Amendments to the Claims

Claims 1-2 (cancelled)

Claim 3 (currently amended) A clamp for a cable support system to suspend an object from an overhead beam comprising:

a generally "C" shaped clamp body;

a threaded fastener threadingly received within one leg of said "C"

shaped body to clamp said "C" shaped body onto overhead beam;

a vertical bore through the vertical position vertical portion of the "C" of said clamp body for the purpose of receiving a cable to be that is suspended from said overhead beam;

a conical end portion at the lower part of said bore;

a wedge retainer vertically movable within said bore;

wedges retained by said wedge retainer for the purpose of contacting to contact

said a cable within said bore and to be forced against said cable by said

conical end portion of said bore when said retainer is at the lower part of

said bore; and

a spring to urge said wedge retainer downwardly relative to said bore.

Claim 4 (currently amended) The clamp of claim 3 wherein the vertical position of said a cable is adjustable by forcing said cable upwardly from the bottom of said bore to release said

Application No. 10/085,543

Amendment date: June 3, 2004

Amendment to Office Action of March 11, 2004

Express Mail No. EL 978301008 US

the wedges release to and permit upward movement of a cable relative to said clamp

when a cable is inserted into the clamp and forced upwardly.

Claim 5 (currently amended) The clamp of claim 4 wherein said wedge retainer has a threaded

portion protruding below said bore with a lock nut threaded onto said wedge retainer

lower portion so that after said a cable is positioned within said clamp "C" shaped body

at the desired height, said lock nut is tightened against said clamp "C" shaped body to

lock said wedge retainer and prevent movement of said wedge retainer relative to said

bore.

Claims 6-7 (cancelled)

Claim 8 (currently amended) A cable support system for hanging an object at a desired distance

below an overhead beam comprising:

a cable;

a clamp having a generally "C" shaped clamp body with a threaded fastener

threadingly received within one leg of said "C" shaped body to clamp said

"C" shaped body onto said overhead beam and a vertical bore through said

clamp body to receive a the cable to be suspended from said overhead

beam, said vertical bore having a conical lower end portion with a wedge

retainer and wedges vertically movable within said bore whereby said

wedges contact said lower conical end portion and said cable to wedge

Page 3 of 12

Application No. 10/085,543

Amendment date: June 3, 2004

Amendment to Office Action of March 11, 2004

Express Mail No. EL 978301008 US

said cable into position within said bore, the vertical position of said cable relative to said bore being vertically adjustable by forcing said cable

upwardly to release said wedges;

an object to be suspended by said cable at a predetermined height below said

beam; and

means for connecting said cable to said object.

Claim 9 (previously presented) The cable support system of claim 8 wherein said means for connecting said cable to said object includes:

a permanent loop formed on the end of said cable; and
passing said cable around said object and thereafter threading said cable through
said permanent loop formed on the end of said cable and thereafter

Claim 10 (previously presented) The cable support system of claim 9 wherein the height of said object below said beam is controlled by the amount of said cable threaded upwardly through said vertical bore in said clamp.

threading said cable into said vertical bore in said clamp.

Claims 11-13 (cancelled)

Application No. 10/085,543

Amendment date: June 3, 2004

Amendment to Office Action of March 11, 2004

Express Mail No. EL 978301008 US

Claim 14 (previously presented) The cable support system of claim 8 wherein said clamp

vertical bore includes a spring that urges said wedge retainer downwardly relative to said

bore.

Claim 15 (previously presented) The cable support system of claim 8 wherein said clamp wedge

retainer has a threaded portion protruding below said bore with a lock nut threaded onto

said wedge retainer lower portion.

Claim 16 (previously presented) The cable support system of claim 10 wherein said clamp

wedge retainer has a threaded portion protruding below said bore with a lock nut threaded

onto said wedge retainer

lower portion so that after said cable is positioned within said clamp "C" shaped body at

the desired height, said lock nut is tightened against said clamp "C" shaped body to

lock said wedge retainer and prevent movement of said wedge retainer relative to said

bore.

Claims 17-22 (canceled)

Page 5 of 12